X-Series – Accessories

- Dust caps for couplings and nipples
- Seal kits for nipples
- Fits all X-Series couplings and nipples

For the X-series we have plastic dust caps, flip dust caps and seal kits available. The dust caps play an important part in prolonging the couplings' life and preventing contamination of your hydraulic system. The seal kits consists of a PUR seal or one O-ring and one backup, depending on the model, for replacement of the front seal in the nipples. The flip dust caps are in general intended for fixed mounted couplings in applications where you want to be sure that the dust cap is on when the coupling is disconnected. Flip dust caps are available in sizes DN10 (3/8") and DN12.5 (1/2").



	Coupling Size			D	2
	ISO - DN	Inch	Dash	Part No.	Description
Seal kits for nipples	6.3	1/4"	-04	10 265 4900	NBR
				10 265 4910	FPM
				10 265 4991	PUR
	10	3/8"	-06	10 365 4900	NBR
				10 365 4910	FPM
				10 365 4991	PUR
	12.5	1/2"	-08	10 565 4900	NBR
				10 565 4910	FPM
				10 565 4991	PUR
	16	5/8"	-10	10 665 4900	NBR
				10 665 4910	FPM
				10 665 4991	PUR
	19	3/4"	-12	10 765 4900	NBR
				10 765 4910	FPM
				10 765 4991	PUR
	25	1"	-16	10 065 4900	NBR
Dust caps	5	1/8"	-02	09 165 1000	For couplings
				09 165 1050	For nipples
	6.3	1/4"	-04	09 265 1000	For couplings
				09 265 1050	For nipples
	10	3/8"	-06	09 365 1000	For couplings
				09 365 1050	For nipples
	12.5	1/2"	-08	09 565 1000	For couplings
				09 565 1050	For nipples
	16	5/8"	-10	09 665 1000	For couplings
				09 665 1050	For nipples
	19	3/4"	-12	09 765 1000	For couplings
				09 765 1050	For nipples
	25	1"	-16	09 065 1000	For couplings
				09 065 1050	For nipples
Flip Dust Cap	10	3/8"	-06 10 365 1010	For counlings	
	12.5	1/2"	-08	10 565 1010 For Couplings	For couplings

CEJN reserves the right to make changes without further notification. Thread connections are listed according to ISO Standards. All measurements are in mm. Check with an authorized CEJN distributor for availability and prices. Please visit our website, www.cejn.com, for general maintenance tips.





